

Solution to Problem Set 5

Date: 18.10.2013

Not graded

Problem 1. Since **BubbleSort** swaps neighboring elements starting from a_1 , if a_1, a_2, \dots, a_k are in decreasing order (i.e., $a_1 > a_2 > \dots > a_k$) then we require the maximum number of computations to sort them. In particular, the number of required operations is given by

$$\sum_{i=1}^{k-1} i = \frac{k(k-1)}{2} = O(k^2).$$

Indeed, at the end of step i , the elements from position $k-i+1$ to position k are already sorted in increasing order by definition of the algorithm. Hence, no more than $k-i-1$ swaps are possible at step $i+1$ and the total number of swaps is upper bounded by $\sum_{i=1}^k (k-i) = \sum_{i=0}^{k-1} i = \frac{k(k-1)}{2}$. The upper bound is achieved in the worst case scenario described above.

Problem 2.

- a) **Algorithm 1** always terminates. **Algorithm 2** terminates if and only if $m \geq 0$.
- b) For **Algorithm 1**, the main loop runs exactly n times, with $j = 1, \dots, n$. For every j , the internal loop runs $m = 2^{j-1}$ times. Thus, the text gets printed $\sum_{j=1}^n 2^{j-1} = 2^n - 1$ times.

Concerning **Algorithm 2**, let us look at the evolution of $\ln m$ (natural logarithm of m). Then, as long as $m > 0$ and if t is initialized to $\ln m$, the algorithm is equivalent to the following:

Algorithm 2'

Require: t : real number

```

1: while  $t > 1$  do
2:    $t \leftarrow t - \ln \frac{3}{2}$ 
3:   print "Hello world"

```

The number of times that Algorithm 2' prints "Hello world" is given by

$$\begin{cases} \left\lceil \frac{t-1}{\ln 3/2} \right\rceil & \text{if } t > 1, \\ 0 & \text{otherwise,} \end{cases}$$

which yields for Algorithm 2 (i.e., for the initial problem)

$$\begin{cases} \left\lceil \frac{\ln m - 1}{\ln 3/2} \right\rceil & \text{if } m > e, \\ 0 & \text{if } 0 \leq m \leq e, \\ \infty & \text{otherwise.} \end{cases}$$

Problem 3.

a) n^2 . Indeed, $f(n) = \sum_{i=0}^n 3i + 1 = 3 \frac{n(n+1)}{2} + n + 1$.

b) n^2 . Indeed, $g(n) = \sum_{i=0}^{n-1} 2i + 1 = 2 \frac{n(n-1)}{2} + n$.

c) n . Indeed, the numerator is a polynomial of degree 4 and the denominator is a polynomial of degree 3.

d) n^4 . Indeed, $h(n) = \sum_{i=0}^{n^2} i = \frac{n^2(n^2+1)}{2}$.

e) n^2 . Indeed, $\lceil n+2 \rceil \leq n+3$ and $\lceil n/3 \rceil n/3 + 1$.

f) n^4 . Indeed, $3n^4 + \log_2 n^8$ is upper bounded by $4n^4$.

Problem 4.

$\frac{1}{n^n}$	$0,0097^n$	$\left(-\frac{1}{2}\right)^n$	n^{-e^4}	$-\frac{1}{\sqrt{n}}$	42	$\log \log \log n$
n	$n \cdot \log \log n$	$n \cdot \log n$	n^{2013}	$n^{\log n}$	$e^{\sqrt{n}}$	2^n
$n \cdot 2^n$	2.0001^n	e^n	$(-3)^n$	e^{2n}	$n!$	

Problem 5.

a) $\left| \frac{3n-8-4n^3}{2n-1} \right| \leq \left| \frac{3n^3+8n^3+4n^3}{2n-n} \right| = 15|n^2|$

b) $1^3 + 2^3 + \dots + n^3 \leq \underbrace{n^3 + n^3 + \dots + n^3}_{n \text{ times}} = n^4$

c) $4^n + n \cdot 2^n \leq 4^n + 4^n = 2 \cdot 4^n$, because $n \leq 2^n$ is true for all n .